

Countertop Basics



Granite, Marble, Quartzite, Soapstone, etc.

- Porous and susceptible to staining needs to be sealed 1-2x per year
- Large color and pattern variability
- May have pits and fissures
- Heat resistant
- Scratch resistant
- Often Resined in the factory to fill small pits & fissures to help strengthen the surface of the material, and to add some stain protection
- Fragile stones will have mesh backing to add strength during transportation and fabrication, important to know for overhangs (1/3 of the current program colors)

Properties Comparing granite, quartzite, and marble (all colors)				
	Granite	Quartzite	Marble	
Hardness	6 to 7	7	3 to 3.5	
Acid resistant?	yes	yes	no	
Porosity	varies	varies	varies	
Hardness of common materials, for reference: fingernail = 2.5 copper penny = 3 glass = 5.5 steel file = 6.5				



Arabian Nights





Thunder White






Bianco Antico





Specific Challenges with Marble



Very soft and can scratch easily



Specific Challenges with Marble



Patina: a natural change in color over time due to oxidation



Specific Challenges with Marble



Etching: Acid reacts with the calcium carbonate and literally eats away a tiny bit of the surface, creating dull spots known as etches. An etch is not a stain. It's an actual changing of the stone itself like a scratch. It's not a discoloration, it's a dulling. Will be less noticeable on Honed vs. Polished surfaces.



Poll taken during a recent fabricator training through the Natural Stone Institute

What challenges have you seen during the fabrication of quartzite?

Poll Results (multiple answers allowed):

Slows Production and Too Long to Fabricate	54%
Water absorption during fabrication	52%
Brusing and chips on seams	45%
Staining after install	57%





Large color variation even in different parts of the same slab



Easily stained by grease

Some colors easily absorb water & can take a month or more to dry




Accent

Tahitian Cream











Manmade Countertops

Quartz

- 80%-92% natural material, remaining is Resin
- Non-porous & Stain Resistant
- Consistent, uniform color & pattern
- Can have resin pooling (blotches)
- Not UV Resistant
- Will crack under heat
- Scratch resistant

Laminate

- Thin hard layer on top of sub wood
- Non-porous
- Stain resistant
- Consistent, uniform color and pattern
- Can burn under heat
- Easy to scratch and chip

Ultra Compact

- Mostly porcelain
- Non-porous
- Stain resistant
- Consistent, uniform color and pattern
- Pattern on surface only
- Heat resistant
- Scratch resistant


Solid Surface

- 100% acrylic and polyester resins
- Non-porous
- Stain resistant
- Consistent, uniform color and pattern
- Can burn and/or crack under heat
- Easy to scratch






Quartz top burn mark




Accent

Thickness & Edges – Natural Stone & Quartz



Thickness & Edges – Ultra Durable

Dekton & Stonemark Porcelain come in 2cm only





Pattern printed on the top


Edge with no pattern



Thickness & Edges – Solid Surface

Solid Surface is built using .5" material but is built up to 1.5" thick using a laminated edge







Backsplash

Backsplash using countertop material can be made in any heights greater than 2" with Quartz and Ultra Compact Surfaces and 3" for Granite. Standard is 4" for Granite & Quartz and 3" for Solid Surface. Also common is "full height" backsplash which goes all the way up to the bottom of the upper cabinets.





backsplash

Example of "full height" backsplash



Captured Backsplash

Captured Backsplash is when the backsplash meets a mirror such as in a bathroom, an outlet, tile backsplash, or some other item.

The Home Depot policy stats that the customer removes their mirror (or other item), we install our standard height backsplash, and then the customer reinstalls their mirror (or other item) on top of the backsplash.

If the customer cannot remove the item, we can measure 1/8" to 1/4" below the item and leave a small gap or for an additional fee we can scribe the backsplash on site (\$175).

The Home Depot What to Expect Document states:

Clear the installation area

Remove all base cabinet contents, drawers and breakables from the installation areas (including but not limited to lamps, vases, mirrors and wall hangings).





Overhangs

Standard overhangs are 1" to 1.5" on all finished sides.

Maximum overhangs for islands, bars, or anything else without supports such as corbels or steel bars are:

- 6" for 2cm Granite
- 10" for 3cm Granite
- 12" for 2cm Quartz
- 12" for 3cm Quartz
- 12" for Ultra Durable

The unsupported portion of the overhang can never be more than 1/3 the width of the entire countertop.



https://accentcountertops.com/overhangs-supports-2/



Common Options & Upgrades

Digital Slab View: A high resolution image of a customer's layout on their actual slab(s): \$250

Chip Minimizer: A bullnose edge around the sink in order to prevent chipping: Kitchen \$250, Vanity \$175

Enhanced Silicone Based Sealer: The industry's best natural stone sealer & we leave the customer with the can: \$150

Radius: A rounded corner. Radius's can range from ¹/₄" to over several feet.

Tear Out and Disposal of existing tops: We can remove and dispose of any countertop material.

Countertop Supports: We can provide and install supports for overhangs for \$200 Retail.

Dishwasher Brackets: We can provide and install Dishwasher Brackets for \$75 Retail.

Oversized Pieces: There is an oversized piece (>20 sq ft) charge of \$250 Retail.

Sinks: We have a number of in stock sinks that we sell through custom line item SKU's.

Waterfall Panels: We charge a custom charge of \$250 per Waterfall Panel.




Accont	Accent				
I would like to view my layout on the material by email prior pushed out, and will be dependent on the day I approve by e Email address:	to fabrication. By selecting this I understand my install date may be email.				
I do not want to view my layout. By selecting this I understand that Accent Interiors will do the layout according to their best judgement					
 The control be index to not point the contertop (i.e. appliance garages, tambut of concer, etc.) need to be removed prior to templating. Cabines that will rest on top of the countertop. Accent Interiors does not remove these items that are integral to your casework. Every effort is made to achieve flat and level countertops. Countertops. Cancent toteriors does not remove these items that are integral to your casework. Every effort is made to achieve flat and level countertops. Countertops. Countertops. Cancent toteriors does not remove these items that are integral to your casework. Every effort is made to achieve flat and level countertops. Countertops. Countertops. Cancent does not remove these items that are integral to your casework. Every effort is made to achieve flat and level countertops. Countertops. Countertops. Countertops. Cancent does not nevel to a set the case of a set on site during the entire installation. Our installers are moving heavy countertops and working with potentially dangerous tools. Please clear countertops, empty lower cabinets, remove top drawers, provide unobstructed access, and avoid the work area. Old countertops, sinks, appliances, etc. should be removed prior to installation unless you have contracted with us to remove them. INCIDENTAL DAMAGE: We will clean the immediate surface areas and leave the job site in "broom swept" condition. Advanced tools are used for dust collection; however, residual dust should be expected. Final wall preparation (i.e. paining, wall papering, etc.) should be completed after the installation. Please tems are consistered individe and are your prepare. TEAR-OUT: If you have contracted us to do tear-out. This includes removal and dispositol your existing gaos, punctures, or main dust and mirrors. Plan the new backsplash to cover or plan to have walls repaired after tear out is complete. Certain restrictions apply. 	Ide not want to view my layout. By selecting this lunderstand that Accert interiors will do the layout according to their best Jugement ARE & MAINTENANCE: Granite countertops needs be sealed approximately every 6-12 months depending on the porousness of nail polish remover, and oil soaps. STRENGTH: Granite is scratch & heat resistant, but we recommend using cutting boards, trivets, & hotp ads. The granite surface or can be damaged by rapid or prolonged heatchange and shar pobjects. Do not place any heat sources directly on the granite surfaces. SINKS; Under mount sink profiles will be cut per the manufacturer's template and recommendations. Top mount sinks will be cut once the countertopare in place on the cabinet to avoid breaking the material during install. BACKSPLASH: BackSplanks are fabricated utiling the same material as the countertops with a "fat polished" edge. A thin bead of silicone will be used to seal the backsplash to the countertop. Plantable lates cauking will be used on the backsplash at the wall. Variations are to be expected along the back of the backsplash. Accent interiors is in traposplicity and integral aps will be visible where the (Inhelphit splashes may require retemplating grafter the countertopack will repair to improve the look of bowed walls. Trapped or full height splashes may require retemplating grafter the countertopacks will need to be removed before the installation by the homeowner/contractor. It will be the homeowner's responsibility to replace wiring, relistant eceptacks, and attach covers. I (print name). I (print name). I (print name). I (print name). Customer Signature: Date:				
Customer Name (Please Print): Customer Signature: Date:					
	Accent Interiors 4103 South 600 West Murray, Utah 64123 801.268 0701 www.accentinitariors.com				
















Digital Layout – Shows Veining







https://accentcountertops.com/digital-slab-view/



Digital Layout – Seams and Options to <u>https://accentcountertops.com/digital-slab-view/</u>







Seams


How does Accent decide where to put a seam?

- Installer safety
- Material safety
- Directional material

- Size of the slabs
- Size of the countertop pieces
- Type of material



Will My Kitchen Sink Fit?



- A Faucet Clearance, typically 4 1/4"

- B Backsplash, typically 1 1/4"
 C Sink Flange, typically 1"
 D Cabinet Faceframe, typically 1"
 E Overhang, typically 1 1/2"

Typical Countertop Depth - 25 1/2" Typical Sink Setback - 4" Largest Sink Cutout with Splash - 16" Largest Sink Cutout without Splash - 17 1/4"



Resources

Natural Stone Institute Articles & Resources

https://usenaturalstone.org/definitive-guide-quartzite/

https://usenaturalstone.org/properties-of-quartzite/

https://usenaturalstone.org/telling-white-stones-apart/

https://usenaturalstone.org/three-things-i-wish-customers-knew-about-usingnatural-stone/

https://usenaturalstone.org/granite-vs-engineered-quartz-countertop/

https://usenaturalstone.org/is-quartz-natural-stone/

https://www.naturalstoneinstitute.org/default/assets/File/consumers/homeowne rsconsumer_countertop.pdf

